



# TRUCK AHEAD OF THE COMPETITION



## **GTL AMT** 6X4 **TRACTOR HEAD**



Fuel Economy | Powerful Engine | Excellent Load Carrier

# SPECIFICATION | FOTON GTL AMT 6X4 Tractor Head

<b>BASIC INFORMATION</b>	Function	Tractor head	<b>GEARBOX</b>	Gearbox Model	12TX2420TD
	Drive Style	6x4		Gearbox Type	AMT□Automated Mechanical Transmission□
	Steering Wheel Position	Left hand		Gearbox Brand	ZF
	Platform	GTL		Numbers of Gears	12 Forward and 2 Reverse
	Vehicle Model	BJ4259SMFKB-AX		PTO	Standard
<b>COMPLETE VEHICLE DIMENSION PARAMETERS</b>	Wheelbase (mm)	3300+1350	<b>BRAKE</b>	Service Brake	Dual circuits pneumatic brake
	Long(mm)	7000		Parking Brake	Energy-accumulating spring air cut-off brake
	Width(mm)	2500		Auxiliary Brake	Engine brake
	Height(mm)	3150	<b>SUSPENSION</b>	Front Suspension/ Leaf Spring Number	Longitudinal leaf spring with dual acting telescopic shock absorbers and anti-roll bar, 9 pieces
<b>COMPLETE VEHICLE MASS PARAMETER</b>	Chassis Kerb Weight(kg)	10435		Rear Suspension/ Leaf Spring Number	Longitudinal leaf spring with balance suspension, 12 pieces
	GCW(t)	90	<b>FRONT AXLE</b>	Capacity(kg)	9000
<b>CABIN</b>	Body Type	Flat roof, all welded steel cab, 4-points spring suspension cab, manual hydraulic cab tilting, adjustable driver's seat(pneumatic seat), seatbelt for driver and co-driver, electric rear-view mirrors and windows, electric heated rearview mirror,central locking, MP3+Radio+USB		Front Axle Brake Type	Drum brakes
			<b>REAR AXLE</b>	Type	Double reduction(central reduction and hub reduction), tandem axle with differential locks between wheels and axles
Carrying Number	2 seats + 1 bunk	Capacity(kg)		2 x 16000	
<b>ENGINE</b>	Engine Model	ISGe3-430	Rear Axle Brake Type	Drum brakes	
	Engine Type	Inline six-cylinder, four-stroke, water cooled, turbocharged, intercooled,direct injection, common rail diesel engine	<b>TYRE</b>	Tyre Size	Standard:315/80R22.5 Optional:13R22.5
	Displacement (cc)	11,800		Numbers of Tyres	10+1
	Max Power (kw/ps/rpm)	316/430/1900	<b>STEERING</b>	Type	Hydraulic steering with power assistance
	Max Torque (Nm/rpm)	2000/1000-1400		Steering Wheel	Adjustable
	Engine Brand	CUMMINS	<b>FUEL TANK</b>	Type	Aluminum fuel tank with lockable cap
	Emission	Euro III		Capacity	700L
<b>CLUTCH</b>	Clutch Type	Single, dry type diaphragm spring	<b>ELECTRICAL SYSTEM</b>	Rated Voltage	24V
	Plate Diameter(mm)	φ430		Battery	2x12V-165Ah
	Operating System	Automatic electric control	<b>OTHER CONFIGURATION</b>	ABS+ASR	Standard
		A/C		Standard	
		Cruise		Standard	
		Fifth Wheel		90#(3.5")	
		ADR		Optional	



**ACCRA**, Graphic Road  
Head office  
South Industrial Area.  
P. O. Box 5216, Accra  
Tel: +233 (244) - 338 393

**ACCRA**, Silver Star Tower  
Ground Floor,  
Airport City, Accra.  
Tel: +233 (302) - 768 849-51

**TEMA**,  
Cocoa Processing Road  
P. O. Box 199, Tema.  
Tel: +233 (243) - 700 751

**KUMASI**,  
P. O. Box 6015 Kumasi  
Prempeh 1 Street Adum.  
Tel: +233 (322) - 030 200

**TAMALE**,  
P. O. Box TL Tamale,  
Kumasi Road.  
Tel: +233 (372) - 022 125

**TAKORADI**,  
P. O. Box MC 257, Paa  
Grant Avenue. Takoradi.  
Tel: +233 (554) - 391 153

foton.sales@japanmotors.com | www.japanmotors.com  
Genuine spare parts and affordable quality service throughout Ghana