

STAY AHEAD OF THE COMPETITION



GTL-E 6X4
TRACTOR HEAD



SPECIFICATION | FOTON GTL E 6X4 Tractor head

BASIC INFORMATION	Function	Tractor head
	Drive Style	6×4
	Steering Wheel Position	Left hand
	Platform	GTL-E
	Vehicle Model	BJ4259SMFKB-26
COMPLETE VEHICLE DIMENSION PARAMETERS	Wheelbase (mm)	3300+1350
	Long(mm)	7000
	Width(mm)	2500
	Height(mm)	3150
COMPLETE VEHICLE MASS PARAMETER	Chassis Kerb Weight(kg)	10200
	GCW(t)	90
CABIN	Body Type	Flat roof, all welded steel cab, 4-points spring suspension cab, manual hydraulic cab tilting, adjustable driver's seat(pneumatic seat), seatbelt for driver and co-driver, manul rearview mirrors and electric windows, central locking, MP3+Radio+USB
	Carrying Number	2 seats + 1 bunk
ENGINE	Engine Model	ISGe3-400
	Engine Type	Inline six-cylinder, four-stroke, water cooled, turbocharged, intercooled,direct injection, common rail diesel engine
	Displacement (cc)	11,800
	Max Power (kw/	
	ps/rpm) `	294/400/1900
	ps/rpm) Max Torque (Nm/rpm)	294/400/1900 2000/1000-1400
	Max Torque (Nm/	
	Max Torque (Nm/rpm)	2000/1000-1400
	Max Torque (Nm/rpm) Engine Brand	2000/1000-1400 CUMMINS
	Max Torque (Nm/rpm) Engine Brand Emission	2000/1000-1400 CUMMINS Euro III Single, dry type diaphragm
сьитсн	Max Torque (Nm/rpm) Engine Brand Emission Clutch Type Plate	2000/1000-1400 CUMMINS Euro III Single, dry type diaphragm spring
сситсн	Max Torque (Nm/rpm) Engine Brand Emission Clutch Type Plate Diameter(mm)	2000/1000-1400 CUMMINS Euro III Single, dry type diaphragm spring ф430 Hydraulic control with air
ССССССССССССССССССССССССССССССССССССССС	Max Torque (Nm/rpm) Engine Brand Emission Clutch Type Plate Diameter(mm) Operating System	2000/1000-1400 CUMMINS Euro III Single, dry type diaphragm spring ф430 Hydraulic control with air pressure assistance

BRAKE	Service Brake	Dual circuits pneumatic brake
	Parking Brake	Energy-accumulating spring air cut-off brake
	Auxiliary Brake	Engine brake
SUSPENSION	Front Suspension/ Leaf Spring Number	Longitudinal leaf spring with dual acting telescopic shock absorbers and anti-roll bar, 9 pieces
	Rear Suspension/ Leaf Spring Number	Longitudinal leaf spring with balance suspension, 12 pieces
FRONT AXLE	Capacity(kg)	9000
	Front Axle BrakeType	Drum brakes
REAR AXLE	Туре	Double reduction(central reduction and hub reduction), tandem axle with differential locks between wheels and axles
	Capacity(kg)	2 x 16000
	Rear Axle Brake Type	Drum brakes
TYRE	Tyre Size	Standard:315/80R22.5 Optional:13R22.5
	Numbers of Tyres	10+1
STEERING	Туре	Hydraulic steering with power assistance
	Steering Wheel	Adjustable
FUEL TANK	Туре	Aluminum fuel tank with lockable cap
	Capacity	700L
ELECTRICAL SYSTEM	Rated Voltage	24V
	Battery	2x12V-165Ah
OTHER CONFIGURATION	ABS+ASR	Optional
	A/C	Standard
	Cruise	Standard
	Fifth Wheel	90#(3.5")
	ADR	Optional



ACCRA, Graphic Road Head office South Industrial Area. P. O. Box 5216, Accra Tel: +233 (244) - 338 393

KUMASI,

P. O. Box 6015 Kumasi Prempeh 1 Street Adum. Tel: +233 (322) - 030 200

ACCRA, Silver Star Tower

Ground Floor, Airport City, Accra. Tel: +233 (302) - 768 849-51

TAMALE,

P. O. Box TL Tamale, Kumasi Road. Tel: +233 (372) - 022 125

TEMA,

Cocoa Processing Road P. O. Box 199, Tema. Tel: +233 (243) - 700 751

TAKORADI,

P. O. Box MC 257, Paa Grant Avenue. Takoradi. Tel: +233 (554) - 391 153