





A dependable service network and safety programs make life with a DT even better!

many people choose the DT, however. Another big reason is the world-standardized network of service and parts supply they are backed by. At Yamaha dealerships, you can get repairs and after-sale service performed by certified and experienced technicians. The global Yamaha service network trains technicians according to the same standardized curriculum used all over the world to ensure that Yamaha machines are kept running in the best possible condition.

What's more, Yamaha operates its Yamaha Riding Academy (YRA) riding safety program to help make sure that owners know how to use their motorcycles properly for maximum safety and enjoyment. Highly trained instructors take the initiative in teaching users proper riding technique using exclusive Yamaha curriculums. There are YRA course curriculums tailored to the specific needs of police, of companies where motorcycles are used daily, and also for owners who want to enjoy leisure riding.



DT125



DARK CYAN METALLIC 8 (DCM8)



BLUISH WHITE COCKTAIL 1 (BWC1)



DEEP PURPLISH BLUE METALLIC C (DPBMC)

DT175



DARK CYAN METALLIC 8 (DCM8)



BLUISH WHITE COCKTAIL 1 (BWC1)



DEEP PURPLISH BLUE METALLIC C (DPBMC)


Introducing Yamaha Genuine Motor Oil



Yamalube is the Yamaha Genuine motor oil recommended for the DT125/175. It has just the right mix of additives to keep your motor running in the best possible condition with a minimum of carbon build-up in the combustion chamber to ensure stable power and fuel economy performance.

Always remember to review your YAMAHA owner's manual. Always ride in a responsible manner, respecting the environment as well as national and local laws. Keep the machine well maintained and always outfitted in accordance with national and local laws. Always wear an approved helmet, eye protection, long-sleeved shirt, long pants, gloves and boots. Yamaha reserves the right to change specifications without notice. Specifications and measurements are approximations and subject to variance. For details, confirm with your dealer before purchase. The riders shown in this brochure are highly skilled in a closed area riding.

Special DT Carrier





Specifications

MA DT125	ENGINE	DT175
Air-cooled, 2-stroke, reed-valve, single	Туре	Air-cooled, 2-stroke, reed-valve, single
123 cm ³	Displacement	171 cm ³
56.0 x 50.0 mm	Bore x stroke	66.0 x 50.0 mm
7.2:1	Compression ratio	6.7:1
11 kW (15 PS) @7,000 r/min	Maximum Power	13 kW (17.5 PS) @7,000 r/min
15 N • m (1.6 kgf • m) @5,500 r/min	Maximum Torque	19 N·m (1.9 kgf·m) @5,500 r/min
Separate lubrication	Lubrication system	Separate lubrication
Carburetor	Carburetor type	Carburetor
CDI	Ignition	CDI
Kick	Starting system type	Kick
10 liters	Fuel tank capacity	10 liters
0.9 liters	Engine oil capacity	0.9 liters
Constant mesh 6-speed	Transmission	Constant mesh 6-speed
Return	Shift type	Return
DT125	CHASSIS	DT175
2,110 mm	Overall length	2,110 mm
865 mm	Overall width	865 mm
1,165 mm	Overall height	1,165 mm
830 mm	Seat height	830 mm
1,340 mm	Wheelbase	1,340 mm
260 mm	Min. ground clearance	260 mm
107 kg	Weight (Wet: with oil and a full fuel tank)	107 kg
Telescopic	Front Suspension	Telescopic
Swingarm	Rear Suspension	Swingarm
Drum	Front Brake	Drum
Drum	Rear Brake	Drum
2.75-21-45P (Tube Type)	Front Tyre	2.75-21-45P (Tube Type)
Ziro Zir ioi (iabo ijpo)		

JAPAN MOTORS TRADING GO. LTD.
P. O. BOX AN 5216 ACCRA PIORTH
TEL: 4233 030292991
CEL: +223 054010657
EMAIL: salesrep1@japanmotors.com



YAMAHA MOTOR CO., LTD. 2500 SHINGAI IWATA SHIZUOKA JAPAN

> 549002 © 0.5-a1 Printed in Japan

Copyright @ Yamaha Motor Co., Ltd. All Rights Reserved